

# ALUMINIUM LOADING RAMPS.

Load safely with Ausramp, the name you know and can trust.

**Standard Ramps sizes:** 3, 4, 4.5, 5, 6 & 8 tonne  
For rubber or steel.

**Machines applicable to ramp index:**

<b>1.5 tonne</b>	To Suit Mini Loaders	
<b>3.425R</b>	Skidsteer Range Mini Backhoes Small Excavators	All on Rubber
<b>4.425R</b>	Skidsteer Range Mini Backhoes Small Excavators	All Rubber
<b>4.5-500R</b>	Wider Version of 4.425R More suited to Excavators	All on Rubber
<b>4.5-500SR</b>	Same as 4.5-500R Designed to carry: Steel Track mini Excavators	On Steel or Rubber
<b>5.510SR</b>	Agriculture Industry Machines Tractors Mini Excavators	On Steel or Rubber
<b>6-610SR</b>	Designed Purposley to carry: Steel Tracked Excavators Steel Tracked Machines Backhoes Larger sized Tractors Front End Loaders	On Steel or Rubber Will NOT Accept Dozer Grouser Plates
<b>8-660SR</b>	Very Robust Ramp: Steel Tracked Excavators Steel Tracked Machines	Will NOT Accept Dozer Grouser Plates



#### TECHNICAL DATA

Product Code	Capacity Per Pair	Weight Per Ramp	Length	Beam Clearance	Height Up To
3-425R	3.0 tonne	30kg	3.5m	325mm	1.2m
4-425R	4.0 tonne	36kg	3.5m	350mm	1.2m
4-425R (3.9)	4.0 tonne	40kg	3.9m	350mm	1.4m
4.5-500SR	4.5 tonne	40kg	3.5m	425mm	1.2m
4.5-500SR (3.9)	4.5 tonne	47kg	3.9m	425mm	1.4m
5.510SR	5.0 tonne	49kg	3.5m	470mm	1.2m
6-610SR	6.0 tonne	55kg	3.5m	500mm	1.2m
8-660SR	8.0 tonne	68kg	3.5m	500mm	1.2m

Code: **R** = Rubber Tracked Machines ONLY a **SR** = Steel & Rubber Tracked Machines  
Height up to 1.2mtrs & 1.4mtrs is only Ausramp's recommended loading height.

Our commitment to continuous evaluation improvement of our products requires that features and specifications may change without notice. Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. \*See your Dealer/Retailer for details. Safety begins with a thorough understanding of the equipment. Always make sure you and all operators read the Operator's manual before using the equipment. Pay close attention to all safety and operation decals.

**Auswide Equipment Pty. Ltd.**

ABN 59 506 564 203

PO Box 438, Somerville Vic 3912

42 Frankston Gardens Drive, Carrum Downs Vic 3201

Telephone (03) 9775 1669 Facsimile (03) 9775 0095

Email [info@ausramp.com](mailto:info@ausramp.com) [www.ausramp.com](http://www.ausramp.com)

